

Product Description

Mobil Almo 500 Series oils are a range of solvent refined paraffinic mineral oils containing emulsifying, anti-wear, anti-rust and adhesive type additives. They have been developed to provide wear and corrosion protection in rock drills and other pneumatic tools used in mining and other industrial applications.

Benefits

Mobil Almo 500 Series oils offer the following benefits:

- Good protection for all reciprocating and rotary parts against corrosion afforded by anti-rust characteristics
- Extended working life of moving parts due to good protection against wear
- Protection against the formation of gummy deposits which cause sluggish valve action is provided by good chemical stability
- Reduced tendency in wet conditions for water wash-off as a result of adhesive properties
- Good low temperatures lubrication with reduced tendencies to icing and few tool stoppages in icing conditions
- Improved working environment due to less fog in confined spaces
- Reduced operating costs following lower maintenance costs and less downtime for repair and replacement

Applications

Mobil Almo 525 is recommended for use as an air line lubricant in most air tool applications both percussive and rotary. It also finds useful application as a winter grade rock drill oil.

Mobil Almo 527 is a general purpose lubricant for lubrication of medium and severe duty air tools used in mine, quarry and civil engineering applications.

Mobil Almo 532 is recommended for severe duty operations in open pit mines, quarries and contractor applications in winter.

Properties

Even in the presence of large amounts of water the Mobil Almo 500 Series oils distribute readily to all moving parts of pneumatic equipment. The adhesive and emulsifying agents encourage the maintenance of continuous oil films to reduce wear and guard against rusting.

The additive materials used have been carefully selected to avoid obnoxious or dangerous odours which can be disagreeable, cause eye burning or nausea. This is particularly important when working in mines and enclosed spaces.

The load carrying property of Mobil 500 Almo Series oils minimises wear on heavily loaded parts and their chemical stability prevents the formation of gummy type deposits and sludges.

Mobil Almo 500 Series oils provide good protection against rust and corrosion in the presence of condensate water. Their low pour points ensure adequate lubrication in the cold environment produced by air expansion - and so guard against icing stoppages.

Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

Product Characteristics

Mobil Almo	525	527	532
ISO Viscosity Grade	46	100	320
Viscosity, cSt at 40°C	46	97	320
Viscosity, cSt at 100°C	6.8	11.3	24
Viscosity Index, min.	90	90	90
Pour Point, °C max.	-30	-27	-18
Flash Point, COC °C min.	209	199	232

Due to continual product research and development, the information contained herein is subject to change without notice

Mobil Oil Company Limited
Acting as Agent for Mobil Lubricants UK Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000

